



Dual fuel heaters can be powered by either propane or natural gas. Simply turn the fuel selector valve to change the fuel supply. The heaters come equipped with an electronic direct spark ignition control and 100% flame safeguard system. Designed for commercial applications including construction and maintenance. Environmentally friendly with minimal products of combustion.



F-400T



F-1000T



F-1500T

MODEL	F-400T	F-1000T	F-1500T
FUEL TYPE	DUAL FUEL - LP/NG	DUAL FUEL - LP/NG	DUAL FUEL - LP/NG
BTU/HR	400,000 MAX.	1,000,000 MAX.	1,500,000 MAX.
CFM	2,000	7,000	7,000
POWER REQUIREMENTS	115V/60HZ/1PH/15A	115V/60HZ/1PH/20A	115V/60HZ/1PH/20A
FUEL CONSUMPTION	4.37 GAL/HR (PROPANE) 400 CFH (GAS)	10.93 GAL/HR (PROPANE) 1,000 CFH (GAS)	16.4 GAL/HR (PROPANE) 1,500 CFH (GAS)
IGNITION	DIRECT SPARK	DIRECT SPARK	DIRECT SPARK
SECOND STAGE REGULATOR	3/4" NPT #B42R0.75	1-1/4" NPT #B42R1.25	1-1/4" NPT #B42R1.25
AIR OUTLET DIA.	15"	26"	26"
L x W x H	48" x 22" x 24"	61" x 29" x 38"	61" x 29" x 38"
WEIGHT	90 LBS	356 LBS	360 LBS

**EASY TO SWITCH
FUEL SUPPLY**