

# ELECTRIC HEATERS



## FOR FLAMELESS OPERATION

Electric heaters operate quietly and are easy to store. No assembly is required and ductwork can be attached to the heater to customize airflow. This heater type exhibits a high outlet air velocity and requires 480V power. Additional features include Inlet guards, outlet guards, and black powder coated finish.



**FLE-60RC**



**FLE-150**

### FEATURES

Camlock Connection

Remote Thermostat

High Static Blower

MODEL	FLE-60RC*	FLE-150*
<b>BTU/HR</b>	60kW SETTING: 205,000 40kW SETTING: 137,000 20kW SETTING: 68,000	150kW SETTING: 512,000 90kW SETTING: 307,000 60kW SETTING: 205,000
<b>CFM</b>	60kW SETTING: 5,200 40kW SETTING: 4,700 20kW SETTING: 4,500 FAN ONLY: 4,700	150kW SETTING: 7,300 90kW SETTING: 6,700 60kW SETTING: 5,400 FAN ONLY: 7,900
<b>NOISE RATING</b>	63 TO 67 dB	76 TO 85 dB
<b>POWER REQUIREMENTS</b>	480V/3PH/75A	480V/3PH/200A
<b>DUCT LENGTH</b>	150'	200'
<b>BLOWER</b>	DIRECT DRIVE	DIRECT DRIVE
<b>DUAL AIR INLET DUAL AIR OUTLET</b>	16" x 16" 18" x 13"	20" (RETURN) 20" (SUPPLY)
<b>L x W x H</b>	32" x 48" x 25.5"	66" x 36" x 40"
<b>WEIGHT</b>	290 LBS	560 LBS

**QUIET AND  
FLEXIBLE  
ELECTRIC  
HEAT**

\*SPECIAL ORDER ONLY - MARCH THRU AUGUST