

TEMPORARY CLIMATE SOLUTIONS

600k INDIRECT FIRED HEATERS

This technology utilizes a heat exchanger that diverts combustion products outside the space through its chimney.

MODEL	HCI-600D	HCI-600D (BULK TANK)	HCI-600G
FUEL TYPE	OIL	OIL	DUAL FUEL- PROPANE/ NG
BTU/HR	550,000	550,000	550,000
CFM	5,200 (Duct up to 150')	5,200 (Duct up to 150')	5,200 (Duct up to 150')
POWER REQUIREMENTS	115V / 20AMP	115V / 20AMP	115V / 20AMP
FUEL TANK CAPACITY*	REMOTE REQUIRED	118 GALLONS	EXTERNAL
RUN TIME*	14.5 HOURS	28.5 HOURS	
FUEL CONSUMPTION*	4.1 GAL/ HR	4.1 GAL/ HR	
HEAT EXCHANGER	16 GA 304 SS	16 GA 304 SS	16 GA 304 SS
AIR OUTLET DIAMETER	(2) 12", (1) 16", (1) 20"	(2) 12", (1) 16", (1) 20"	(2) 12", (1) 16", (1) 20"
AIR INLET DIAMETER	(1) 16" - RETURN AIR	(1) 16" - RETURN AIR	(1) 16" - RETURN AIR
BURNER TECHNOLOGY	RIELLO OR BECKET BURNER	RIELLO OR BECKET BURNER	RIELLO OR BECKET BURNER
THERMOSTAT	25' CORD FOR REMOTE LOCATION	25' CORD FOR REMOTE LOCATION	25' CORD FOR REMOTE LOCATION
STACKABLE FRAME	YES	N/A	YES
BLOWER	BACKWARD INCLINE DIRECT DRIVE	BACKWARD INCLINE DIRECT DRIVE	BACKWARD INCLINE DIRECT DRIVE
L x W x H	81" x 33" x 74"	77" x 33" x 71"	81" x 33" x 74"
WEIGHT	695 LBS	1,075 LBS	655 LBS
*BASED ON 100% INPUT CAPACITY			

